

View Online at <https://aerobasegroup.com/nsn/5315-01-375-3032>

Shank Diameter:

Between 0.1870 inches and 0.1895 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

5150 double pounds per square inch

Shoulder To Head End Distance:

1.550 inches

Pin Center To Handle End Distance:

1.780 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shank astm 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0