## NSN 5315-01-376-1044

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-376-1044

First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 2b **Thread Direction:** Right-hand Thread Length: 0.2000 inches **Shoulder Diameter:** 0.2500 inches **Overall Length:** 0.8090 inches First Step Diameter: Between 0.1820 inches and 0.1840 inches **Second Step Diameter:** Between 0.1820 inches and 0.1840 inches **Second Step Length:** 2.0000 inches **Third Step Diameter:** 0.1640 inches Third Step Length: Between 0.1820 inches and 0.1840 inches **Shoulder Length:** 0.0590 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.1640 inches **First End Location:** Tapered end First End Taper Angle: 30.0 degrees First End Tip Radius: 0.0300 inches Material: Steel comp 303

**Material Specification:** 

Astm-a582 assn standard single material response

## NSN 5315-01-376-1044

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment:                                      |
|---|
| Passivate   |
| Surface Treatment Specification:                        |
| Qq-p-35 federal specification single treatment response |
| Style Designator:                                       |
| Shoulder  |
| Thread Series Designator:                               |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:                                       |
| No  |
| Fiig:   |

A212a0