

View Online at <https://aerobasegroup.com/nsn/5315-01-376-1045>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.4050 inches

**Shank Length:**

0.5925 inches

**Shoulder Diameter:**

0.4380 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Overall Length:**

1.2175 inches

**Second End Taper Length:**

Between 0.2480 inches and 0.2520 inches

**Thready Qty Per Inch (tpi):**

28

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.2500 inches

**Second Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Second End Tip Radius:**

Between 0.0600 inches and 0.0900 inches

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.5000 inches

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Mil-t-9047, type 3, cond. A military specification single material response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-9047 spec.