## NSN 5315-01-376-1045

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-376-1045

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

За

## **Thread Direction:**

**Right-hand** 

Thread Length:

0.4050 inches

Shank Length:

0.5925 inches

Shoulder Diameter:

0.4380 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

**Overall Length:** 

1.2175 inches

Second End Taper Length:

Between 0.2480 inches and 0.2520 inches

Thready Qty Per Inch (tpi):

28

Second End Relationship With First End:

Not identical

Thread Size:

0.2500 inches

Second Shank Diameter:

Between 0.2490 inches and 0.2495 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Tip Radius:

Between 0.0600 inches and 0.0900 inches

Second End Taper Angle:

45.0 degrees

Second Shank Length:

0.5000 inches

Material:

Titanium alloy uns r56400

## **Material Specification:**

Mil-t-9047, type 3, cond. A military specification single material response

## NSN 5315-01-376-1045

Headless Shoulder Pin - Page 2 of 2

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-9047 spec.

