

View Online at <https://aerobasegroup.com/nsn/5315-01-386-6065>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered and counterbored

**Overall Length:**

8.120 inches

**Diameter:**

Between 1.9975 inches and 1.9985 inches

**Effective Length:**

7.620 inches

**Undercut Diameter:**

Between 1.881 inches and 1.891 inches

**Undercut Width:**

Between 0.068 inches and 0.072 inches

**Second Undercut Width:**

Between 0.068 inches and 0.072 inches

**End Application:**

2330-01-303-8832 m1000 chettl trailer

**Second End Counterbore Diameter:**

0.870 inches

**Second End Counterbore Depth:**

0.500 inches

**First End Taper Length:**

Between 0.040 inches and 0.070 inches

**Second End Taper Length:**

Between 0.040 inches and 0.070 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

55.0 rockwell c and 62.0 rockwell c

**First End Location:**

Unthreaded end

**First End Taper Angle:**

30.0 degrees

**Second End Taper Angle:**

30.0 degrees

**Material:**

Steel comp 8620

**Material Specification:**

Astm a322 assn standard single material response or astm a331 assn standard single material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074e, class 2, grade a military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-26074e spec.