

View Online at <https://aerobasegroup.com/nsn/5315-01-386-6065>

First End Style:

Chamfered

Second End Style:

Chamfered and counterbored

Overall Length:

8.120 inches

Diameter:

Between 1.9975 inches and 1.9985 inches

Effective Length:

7.620 inches

Undercut Diameter:

Between 1.881 inches and 1.891 inches

Undercut Width:

Between 0.068 inches and 0.072 inches

Second Undercut Width:

Between 0.068 inches and 0.072 inches

End Application:

2330-01-303-8832 m1000 chettl trailer

Second End Counterbore Diameter:

0.870 inches

Second End Counterbore Depth:

0.500 inches

First End Taper Length:

Between 0.040 inches and 0.070 inches

Second End Taper Length:

Between 0.040 inches and 0.070 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

55.0 rockwell c and 62.0 rockwell c

First End Location:

Unthreaded end

First End Taper Angle:

30.0 degrees

Second End Taper Angle:

30.0 degrees

Material:

Steel comp 8620

Material Specification:

Astm a322 assn standard single material response or astm a331 assn standard single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074e, class 2, grade a military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-c-26074e spec.