## NSN 5315-01-387-4379

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-387-4379

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.874 inches
Shank Length:
0.874 inches
Shoulder Width Across Flats:
Between 0.850 inches and 0.875 inches
Overall Length:
1.620 inches
Undercut Width:
0.130 inches
End Application:
Mount, machine gun, mk93, mod 0
First End Taper Length:
0.030 inches
Second End Taper Length:
0.060 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.625 inches
Second Shank Diameter:
0.755 inches
First End Location:
Unthreaded end
First End Taper Angle:
45.0 degrees
Second End Taper Angle:
60.0 degrees
Second Shank Length:
0.426 inches
Material:
Steel comp 303
Surface Treatment:

Oxide

## NSN 5315-01-387-4379

Headless Shoulder Pin - Page 2 of 2



## Surface Treatment Specification:

Mil-c-13924, class 4 military specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-13924 spec.