

View Online at <https://aerobasegroup.com/nsn/5315-01-388-0158>

First End Style:

Square

Head Style:

Bevel

Under Head Length:

Between 0.940 inches and 1.010 inches

First Step Diameter:

Between 0.411 inches and 0.421 inches

First Step Length:

Between 0.580 inches and 0.620 inches

Second Step Diameter:

Between 0.323 inches and 0.327 inches

Second Step Length:

0.140 inches

Third Step Diameter:

0.164 inches

Third Step Length:

Between 0.360 inches and 0.390 inches

Internal Drive Style:

Torque

End Application:

Pacer dawn

Hardness Rating:

28.0 rockwell c and 40.0 rockwell c

Pin Head Diameter:

Between 0.411 inches and 0.421 inches

Special Features:

Area 0.360/0.390 by 0.164 is threaded 0.164-32 unc-3a: next assembly 801254: used on 804800

Height:

Between 0.137 inches and 0.157 inches

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 11 federal specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0