

View Online at <https://aerobasegroup.com/nsn/5315-01-388-0158>

**First End Style:**

Square

**Head Style:**

Bevel

**Under Head Length:**

Between 0.940 inches and 1.010 inches

**First Step Diameter:**

Between 0.411 inches and 0.421 inches

**First Step Length:**

Between 0.580 inches and 0.620 inches

**Second Step Diameter:**

Between 0.323 inches and 0.327 inches

**Second Step Length:**

0.140 inches

**Third Step Diameter:**

0.164 inches

**Third Step Length:**

Between 0.360 inches and 0.390 inches

**Internal Drive Style:**

Torque

**End Application:**

Pacer dawn

**Hardness Rating:**

28.0 rockwell c and 40.0 rockwell c

**Pin Head Diameter:**

Between 0.411 inches and 0.421 inches

**Special Features:**

Area 0.360/0.390 by 0.164 is threaded 0.164-32 unc-3a: next assembly 801254: used on 804800

**Height:**

Between 0.137 inches and 0.157 inches

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 11 federal specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0