

View Online at <https://aerobasegroup.com/nsn/5315-01-388-6272>

**First End Style:**

Chamfered

**Second End Style:**

Radius

**Pinlength:**

Between 1.740 inches and 1.760 inches

**Pindiameter:**

Between 0.3126 inches and 0.3128 inches

**Second End Corner Radius:**

Between 0.039 inches and 0.104 inches

**First End Taper Length:**

0.375 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

47.0 rockwell c and 58.0 rockwell c

**Shear Strength:**

20000 double pounds per square inch

**First End Taper Angle:**

Between 4.0 degrees and 16.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Special Features:**

Radius end may be chamfered 25.0 degrees.

**Material:**

Steel

**Material Specification:**

Astm a29 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class 1 military specification single treatment response

**Specification Data:**

96906-ms16555 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-13924 spec.