## NSN 5315-01-388-6272

Headless Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-388-6272 First End Style: Chamfered **Second End Style:** Radius Pinlength: Between 1.740 inches and 1.760 inches Pindiameter: Between 0.3126 inches and 0.3128 inches **Second End Corner Radius:** Between 0.039 inches and 0.104 inches First End Taper Length: 0.375 inches **Features Provided:** Casehardened Second End Relationship With First End: Not identical **Hardness Rating:** 47.0 rockwell c and 58.0 rockwell c **Shear Strength:** 20000 double pounds per square inch First End Taper Angle: Between 4.0 degrees and 16.0 degrees Surface Finish: 16.0 microinches outside diameter **Special Features:** Radius end may be chamfered 25.0 degrees. Material: Steel **Material Specification:** Astm a29 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 1 military specification single treatment response **Specification Data:** 96906-ms16555 government standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5315-01-388-6272

Headless Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-c-13924 spec.