## NSN 5315-01-388-6272

Headless Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-388-6272

First End Style:
Chamfered
Second End Style:
Radius
Pinlength:
Between 1.740 inches and 1.760 inches
Pindiameter:
Between 0.3126 inches and 0.3128 inches
Second End Corner Radius:
Between 0.039 inches and 0.104 inches
First End Taper Length: 0.375 inches
Features Provided:
Casehardened
Second End Relationship With First End:
Not identical
Hardness Rating:
47.0 rockwell c and 58.0 rockwell c
Shear Strength:
20000 double pounds per square inch
First End Taper Angle:
Between 4.0 degrees and 16.0 degrees
Surface Finish:
16.0 microinches outside diameter
Special Features:
Radius end may be chamfered 25.0 degrees.
Material:
Steel
Material Specification:
Astm a29 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 1 military specification single treatment response
Specification Data:
96906-ms16555 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5315-01-388-6272

Headless Straight Pin - Page 2 of 2

**Fiig:** A212a0

Mil-std (military Standard):

Mil-c-13924 spec.

