## NSN 5315-01-388-8496

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-388-8496

| First End Style:  |
|---|
| Chamfered   |
| Second End Style:   |
| Round   |
| First Step Diameter:  |
| Between 1.248 inches and 1.250 inches   |
| First Step Length:  |
| 4.847 inches  |
| Second Step Diameter:   |
| 1.000 inches  |
| Second Step Length:   |
| 4.800 inches  |
| Third Step Diameter:  |
| 0.500 inches  |
| Third Step Length:  |
| 0.723 inches  |
| Hole Arrangement Style:   |
| One end drilled   |
| First Hole Diameter:  |
| Between 0.188 inches and 0.192 inches   |
| First End Taper Length:   |
| 0.060 inches  |
| Second End Relationship With First End:   |
| Not identical   |
| First End Location:   |
| Small end   |
| First End Taper Angle:  |
| 45.0 degrees  |
| Second End Outer Radius:  |
| 0.250 inches  |
| Special Features:   |
| Two holes located on second step 0.510 in. Min 0.520 in. Maximum plus a 2.670 in. Long slot |
| Material:   |
| Steel comp 4140   |
| Material Specification:   |
| Mil-s-5626, cond f military specification single material response                          |
| Surface Treatment:  |
| Phosphate manganese   |
| Style Designator:   |
| Shoulder  |
| Shelf Life:   |
| N/a   |

## NSN 5315-01-388-8496

Headless Shoulder Pin - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5626 spec.

