

View Online at <https://aerobasegroup.com/nsn/5315-01-389-6396>

**First End Style:**

Chamfered

**Second End Style:**

Radius

**Pinlength:**

Between 2.090 inches and 3.010 inches

**Pindiameter:**

Between 0.6251 inches and 0.6253 inches

**Second End Corner Radius:**

Between 0.078 inches and 0.208 inches

**First End Taper Length:**

0.750 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 42.0 rockwell c

**Shear Strength:**

45000 double pounds per square inch

**First End Taper Angle:**

Between 4.0 degrees and 16.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Special Features:**

Hardness of 75-83hrb or equivalent for type 303 steel.

**Material:**

Steel comp 303 or steel comp 416 or steel comp 410

**Material Specification:**

Astm a582 assn standard single material response or astm a493 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Specification Data:**

96906-ms16555 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-p-21143 spec.