## NSN 5315-01-395-5074



Quick Release Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-395-5074 **Head Diameter:** Between 0.410 inches and 0.590 inches **Shank Diameter:** Between 0.3095 inches and 0.3110 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 0.700 inches and 0.720 inches **Actuation Type:** Push Hardness Rating: 40.0 rockwell c spindle **Shear Strength:** 14400 double pounds per square inch **Shoulder To Head End Distance:** 0.830 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.300 inches and 0.330 inches Material: Steel comp 631 spring or steel comp 302 spring **Material Specification:** Qq-w-423 federal specification single material response ring **Surface Treatment: Passivate Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response
Style Designator:
Ring handle
Specification Data:
96906-ms17987 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5315-01-395-5074

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-23460 spec.