

View Online at <https://aerobasegroup.com/nsn/5315-01-397-1788>

First End Style:

Chamfered

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.690 inches

Shank Length:

0.810 inches

Shoulder Diameter:

Between 0.995 inches and 1.005 inches

Shank Diameter:

Between 0.619 inches and 0.624 inches

Overall Length:

3.410 inches

Undercut Diameter:

0.500 inches

Undercut Width:

0.120 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.255 inches and 0.275 inches

Distance From Centerline Of Hole To End Of Pin:

0.373 inches

First End Taper Length:

0.060 inches

Second End Relationship With First End:

Identical

Thread Size:

0.625 inches

Second Shank Diameter:

Between 0.619 inches and 0.624 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second Shank Length:

2.480 inches

Material:

Steel comp 1030 or steel comp 1031 or steel comp 1033 or steel comp 1035 or steel comp 1036 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1137 or steel comp 1138 or steel comp 1139 or steel comp 1140 or steel comp 1141

Surface Treatment:

Zinc alloy or cadmium and chromate

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0