

View Online at <https://aerobasegroup.com/nsn/5315-01-408-4110>

**Head Diameter:**

Between 0.360 inches and 0.450 inches

**Handle Length:**

Between 1.375 inches and 1.750 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Detent Quantity:**

2

**Lanyard Length:**

6.000 inches

**Actuation Method:**

Handle

**Grip Length:**

2.500 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

9200 double pound

**Shoulder To Head End Distance:**

1.030 inches

**Pin Attachment Type:**

Cable lanyard w/terminations and link or ring

**Detent To Tapered End Distance:**

0.410 inches

**Special Features:**

Identification tag attach plus warning streamer

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0