

View Online at <https://aerobasegroup.com/nsn/5315-01-411-7156>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.580 inches

Shank Length:

0.872 inches

Shoulder Width Across Flats:

Between 0.740 inches and 0.760 inches

Shank Diameter:

Between 0.4925 inches and 0.4930 inches

Overall Length:

1.827 inches

First End Taper Length:

0.050 inches

Second End Taper Length:

Between 0.415 inches and 0.455 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.500 inches

Second Shank Diameter:

Between 0.4985 inches and 0.4995 inches

First End Location:

Unthreaded end

First End Taper Angle:

45.0 degrees

Second End Tip Radius:

Between 0.060 inches and 0.090 inches

Second Shank Length:

0.830 inches

Material:

Steel comp 302 or steel comp 303se or steel comp 304

Material Specification:

Qq-s-763, cond b federal specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0