## NSN 5315-01-411-7156

First End Style: Chamfered

Second End Style:

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-411-7156

Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.580 inches
Shank Length:
0.872 inches
Shoulder Width Across Flats:
Between 0.740 inches and 0.760 inches
Shank Diameter:
Between 0.4925 inches and 0.4930 inches
Overall Length:
1.827 inches
First End Taper Length:
0.050 inches
Second End Taper Length:
Between 0.415 inches and 0.455 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.500 inches
Second Shank Diameter:
Between 0.4985 inches and 0.4995 inches
First End Location:
Unthreaded end
First End Taper Angle:
45.0 degrees
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
0.830 inches
Material:
Steel comp 302 or steel comp 303se or steel comp 304
Material Specification:
Qq-s-763, cond b federal specification all material responses
Surface Treatment:
Passivate

## NSN 5315-01-411-7156

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A212a0