NSN 5315-01-417-5731

Spring Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-417-5731

Overall Length: 0.562 inches Diameter: Between 0.098 inches and 0.103 inches Expanded Diameter: Between 0.098 inches and 0.103 inches Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator: Coiled	
Diameter: Between 0.098 inches and 0.103 inches Expanded Diameter: Between 0.098 inches and 0.103 inches Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Between 0.098 inches and 0.103 inches Expanded Diameter: Between 0.098 inches and 0.103 inches Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Expanded Diameter: Between 0.098 inches and 0.103 inches Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Between 0.098 inches and 0.103 inches Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Hardness Rating: 46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
46.0 rockwell c and 53.0 rockwell c Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Shear Strength: 1000 double pounds per square inch Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Material: Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Steel comp 1070 or steel comp 1071 or steel comp 1072 or steel comp 1074 or steel comp 1075 or steel comp 1078 or steel comp or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
or steel comp 1084 or steel comp 1085 or steel comp 1086 or steel comp 1090 or steel comp 1095 Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Material Specification: 66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	1080
66 federal standard all material responses Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Qq-p-416, type 2, cl 3 federal specification single treatment response Style Designator:	
Style Designator:	
Coiled	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A212a0	