NSN 5315-01-421-2064

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-421-2064 First End Style: Chamfered **Head Style:** Flat **Under Head Length:** 1.940 inches First Step Diameter: Between 0.730 inches and 0.770 inches First Step Length: 0.250 inches **Second Step Diameter:** Between 0.623 inches and 0.624 inches Second Step Length: 1.690 inches **Hole Arrangement Style:** One end w/two drilled holes First Hole Diameter: Between 0.104 inches and 0.114 inches **Second Hole Diameter:** Between 0.104 inches and 0.114 inches **Distance From Centerline Of Hole To End Of Pin:** 1.810 inches First End Taper Length: Between 0.080 inches and 0.120 inches First End Taper Angle: Between 12.0 degrees and 18.0 degrees Pin Head Diameter: Between 0.730 inches and 0.770 inches **Angle Between Centerline Of Holes:** Between 85.0 degrees and 95.0 degrees **Special Features:** With groove under head 0.610 min, 0.650 maximum dia: width 0.110 in.Min, 0.130 in. Max Height: Between 0.110 inches and 0.130 inches Material: Steel **Surface Treatment:** Nickel **Style Designator:** Shoulder

N/a

Shelf Life:

NSN 5315-01-421-2064

Headed Shoulder Pin - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0