

View Online at <https://aerobasegroup.com/nsn/5315-01-423-4969>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.305 inches

Shank Length:

0.520 inches

Shoulder Width Across Flats:

0.375 inches

Shank Diameter:

0.190 inches

Overall Length:

1.230 inches

End Application:

F-16

First End Corner Radius:

0.050 inches

First End Taper Length:

0.050 inches

Second End Taper Length:

0.210 inches

Thready Qty Per Inch (tpi):

32

Second End Relationship With First End:

Not identical

Thread Size:

0.190 inches

Second Shank Diameter:

Between 0.188 inches and 0.189 inches

First End Location:

Chamfered end

First End Taper Angle:

45.0 degrees

Second End Tip Radius:

0.060 inches

Surface Finish:

125.0 microinches

Second Shank Length:

0.710 inches

Material:

Steel comp 302

Material Specification:

Mil-s-7720, comp 302, cond b military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-7720 spec.