## NSN 5315-01-424-9563



Quick Release Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-424-9563 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.200 inches and 1.220 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature **Hardness Rating:** 54.0 rockwell c detent and 64.0 rockwell c detent **Shear Strength:** 9200 double pounds per square inch **Shoulder To Head End Distance:** 1.730 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.410 inches Material: Steel comp 631 spring **Material Specification:** 

Qq-w-423 federal specification 1st material response spring or ams5673 assn standard 2nd material response spring

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Style Designator:

Ring handle

**Specification Data:** 

80205-nas1353 through 1366 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5315-01-424-9563

Quick Release Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7720 spec.