NSN 5315-01-426-1954

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-426-1954

| First End Style: | |
|---|--|
| Radius | |
| Second End Style: | |
| Radius | |
| Shank Length: | |
| 5.080 inches | |
| Shoulder Diameter: | |
| Between 2.545 inches and 2.555 inches | |
| Shank Diameter: | |
| Between 2.290 inches and 2.300 inches | |
| Overall Length: | |
| 10.000 inches | |
| End Application: | |
| C-130 mlg t.O. 4a2-9-3, fig 10-1 | |
| First End Corner Radius: | |
| 0.100 inches | |
| Second End Corner Radius: | |
| 0.100 inches | |
| Second End Relationship With First End: | |
| Not identical | |
| First End Location: | |
| Small end | |
| Special Features: | |
| Centered hole diameter 1.100 in by 10.000 in long | |
| Material: | |
| Steel comp 4340 | |
| Material Specification: | |
| Ams 6414 assn standard single material response | |
| Style Designator: | |
| Shoulder | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A212a0 | |