## NSN 5315-01-431-2255



Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-431-2255 First End Style: Chamfered **Second End Style:** Chamfered **Shank Length:** 15.250 inches **Shoulder Width Across Flats:** 9.500 inches **Shank Diameter:** Between 5.030 inches and 5.150 inches **Overall Length:** 24.250 inches First End Taper Length: 0.500 inches **Second End Taper Length:** 4.750 inches Second End Relationship With First End: Not identical **Second Shank Diameter:** Between 5.380 inches and 5.620 inches **First End Location:** Unthreaded end First End Taper Angle: 45.0 degrees **Second End Taper Angle:** 15.0 degrees Second Shank Length: 6.000 inches **Special Features:** Self-locking elelment shall be a patch of nylon 6/6 in accordance with I-p-410, m5.0x0.8-6lg threads Material: Steel comp 630 **Material Specification:** Astm a564 assn standard single material response **Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Mil-f-14072, e300 military specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

## NSN 5315-01-431-2255

Headless Shoulder Pin - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.