

View Online at <https://aerobasegroup.com/nsn/5315-01-431-3175>

First End Style:

Square internally threaded

Second End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.500 inches and 0.531 inches

Taper Length:

Between 1.609 inches and 1.641 inches

Taper Minor Diameter:

Between 0.353 inches and 0.357 inches

Taper Major Diameter:

Between 0.400 inches and 0.435 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.076 inches and 0.086 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.172 inches and 0.203 inches

Grip Length:

Between 1.484 inches and 1.516 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.312 inches

Taper:

0.500 per foot in inches

First End Location:

Tapered end

Material:

Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

Qq-s-689 federal specification 1st material response or il-s-6049 federal standard 10th material response or il-s-6050 military specification 10th material response or il-s-6098 military standard 10th material response or il-s-6758 mfr ref 10th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

spec.