## NSN 5315-01-431-3175

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-431-3175

First End Style:
Square internally threaded
Second End Style:
Square
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.500 inches and 0.531 inches
Taper Length:
Between 1.609 inches and 1.641 inches
Taper Minor Diameter:
Between 0.353 inches and 0.357 inches
Taper Major Diameter:
Between 0.400 inches and 0.435 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
Between 0.172 inches and 0.203 inches
Grip Length:
Between 1.484 inches and 1.516 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.312 inches
Taper:
0.500 per foot in inches
First End Location:
Tapered end
Material:
Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130
Material Specification:
Qq-s-689 federal specification 1st material response or il-s-6049 federal standard 10th material response or il-s-6050 military specification
10th material response or il-s-6098 military standard 10th material response or il-s-6758 mfr ref 10th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response

**Style Designator:**Threaded at small end

## NSN 5315-01-431-3175

Threaded Tapered Pin - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):

spec.