

View Online at <https://aerobasegroup.com/nsn/5315-01-435-6442>

Head Diameter:

Between 0.660 inches and 0.720 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

Between 5.500 inches and 6.500 inches

Actuation Method:

Lever

Grip Length:

Between 1.060 inches and 1.080 inches

Actuation Type:

Pull

Hardness Rating:

58.8 rockwell c detent and 62.0 rockwell c detent

Shear Strength:

36800 double pounds per square inch

Shoulder To Head End Distance:

1.500 inches

Pin Center To Handle End Distance:

1.045 inches

Pin Attachment Type:

Cable lanyard w/o terminations

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

Qq-s-763 federal specification single material response head

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Cam lever

Specification Data:

84256-blc8cl manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0