

View Online at <https://aerobasegroup.com/nsn/5315-01-435-6442>

**Head Diameter:**

Between 0.660 inches and 0.720 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 5.500 inches and 6.500 inches

**Actuation Method:**

Lever

**Grip Length:**

Between 1.060 inches and 1.080 inches

**Actuation Type:**

Pull

**Hardness Rating:**

58.8 rockwell c detent and 62.0 rockwell c detent

**Shear Strength:**

36800 double pounds per square inch

**Shoulder To Head End Distance:**

1.500 inches

**Pin Center To Handle End Distance:**

1.045 inches

**Pin Attachment Type:**

Cable lanyard w/o terminations

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

Qq-s-763 federal specification single material response head

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Cam lever

**Specification Data:**

84256-blc8cl manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0