NSN 5315-01-442-3634

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-442-3634

| First End Style: |
|---|
| Chamfered |
| Second End Style: |
| Square internally threaded |
| Shank Length: |
| 1.531 inches |
| Shoulder Width Across Flats: |
| 0.562 inches |
| Shank Diameter: |
| Between 0.4912 inches and 0.4940 inches |
| Overall Length: |
| 4.125 inches |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| 0.218 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.250 inches |
| First End Taper Length: |
| 0.062 inches |
| Second End Relationship With First End: |
| Not identical |
| First End Location: |
| Shank end |
| First End Taper Angle: |
| 45.0 degrees |
| Material: |
| Steel comp 630 |
| Material Specification: |
| Astm a564 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Shoulder |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5315-01-442-3634

Headless Shoulder Pin - Page 2 of 2

Fiig: A212a0

