

View Online at <https://aerobasegroup.com/nsn/5315-01-457-0002>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.250 inches and 0.280 inches

**Shank Length:**

Between 0.250 inches and 0.280 inches

**Shoulder Diameter:**

0.375 inches

**Shank Diameter:**

0.250 inches

**Overall Length:**

1.580 inches

**Second End Slot Width:**

Between 0.068 inches and 0.088 inches

**First End Taper Length:**

0.040 inches

**Second End Slot Depth:**

Between 0.060 inches and 0.090 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.250 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Second End Outer Radius:**

0.090 inches

**Material:**

Steel comp 1010 or steel comp 1025

**Material Specification:**

Astm a576 comp 1010 through 1025 assn standard single material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 assn standard single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0