## NSN 5315-01-459-1522

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-459-1522

First End Style:

Square

Second End Style:

Chamfered

Thread Class:

2a

## **Thread Direction:**

**Right-hand** 

**Thread Length:** 

0.305 inches

Shank Length:

0.305 inches

Shoulder Diameter:

0.250 inches

Shank Diameter:

## 0.138 inches

Overall Length:

1.070 inches

**Undercut Diameter:** 

0.210 inches

Undercut Width:

Between 0.060 inches and 0.090 inches

Second Undercut Width:

0.405 inches

Second Undercut Diameter:

0.125 inches

Second End Taper Length:

0.395 inches

Thready Qty Per Inch (tpi):

32

Second End Relationship With First End:

Not identical

Thread Size:

0.138 inches

Second Shank Diameter:

Between 0.187 inches and 0.188 inches

First End Location:

Threaded end

Second End Tip Radius:

0.030 inches

Second End Taper Angle:

60.0 degrees

## NSN 5315-01-459-1522

Headless Shoulder Pin - Page 2 of 2



Second Shank Length: 0.315 inches Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Undercut

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0