NSN 5315-01-462-2686

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-462-2686

View Online at https://aerobasegroup.com/nsn/5315-01-462-2686
First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.530 inches
Shoulder Width Across Flats:
Between 0.430 inches and 0.439 inches
Shank Diameter:
0.189 inches
Overall Length:
Between 1.131 inches and 1.151 inches
Second End Taper Length:
Between 0.288 inches and 0.308 inches
Thready Qty Per Inch (tpi):
32
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.302 inches and 0.322 inches
First End Location:
Threaded end
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
Between 0.476 inches and 0.496 inches
Material:
Steel comp 302 or steel comp 304 or steel comp 303se
Material Specification:
Qq-s-763 cond b federal specification 1st material response or qq-s-763 cond b federal specification 2nd material response or mms265
cond b fscm 76301 mfr ref 3rd material response
Surface Treatment:

Surface Treatment Specification:

Passivate

Ams qq-p-35 assn standard single treatment response

NSN 5315-01-462-2686

Headless Shoulder Pin - Page 2 of 2



Style	Design	nator:
Otylo	Design	ilatoi.

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A212a0