

View Online at <https://aerobasegroup.com/nsn/5315-01-466-7234>

**First End Style:**

Chamfered

**Head Style:**

Flush

**Under Head Length:**

Between 8.690 inches and 8.810 inches

**First Step Diameter:**

Between 0.7568 inches and 0.7572 inches

**First Step Length:**

Between 1.520 inches and 1.580 inches

**Second Step Diameter:**

0.757 inches

**Second Step Length:**

4.900 inches

**Third Step Diameter:**

Between 0.7568 inches and 0.7572 inches

**Third Step Length:**

1.100 inches

**End Application:**

Lightarmoredvehicle

**Hardness Rating:**

33.0 rockwell c and 38.0 rockwell c

**Pin Head Diameter:**

0.625 inches

**Special Features:**

Allsharpedgesandcornersshallbeboken.003to.015unlessotherwisepecified; n0.4maxcenterdrilloptional; partshallbemagneticparticleinspectediawmil-std-1949nocracks, seamsorlapsallowed

**Height:**

Between 0.250 inches and 0.280 inches

**Material:**

Stainless steel

**Material Specification:**

Ams5659 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-std-171 spec.