

View Online at <https://aerobasegroup.com/nsn/5315-01-466-7234>

First End Style:

Chamfered

Head Style:

Flush

Under Head Length:

Between 8.690 inches and 8.810 inches

First Step Diameter:

Between 0.7568 inches and 0.7572 inches

First Step Length:

Between 1.520 inches and 1.580 inches

Second Step Diameter:

0.757 inches

Second Step Length:

4.900 inches

Third Step Diameter:

Between 0.7568 inches and 0.7572 inches

Third Step Length:

1.100 inches

End Application:

Lightarmoredvehicle

Hardness Rating:

33.0 rockwell c and 38.0 rockwell c

Pin Head Diameter:

0.625 inches

Special Features:

Allsharpedgesandcornersshallbeboken.003to.015unlessotherwisepecified; n0.4maxcenterdrilloptional; partshallbemagneticparticleinspectediawmil-std-1949nocracks, seamsorlapsallowed

Height:

Between 0.250 inches and 0.280 inches

Material:

Stainless steel

Material Specification:

Ams5659 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-std-171 spec.