

View Online at <https://aerobasegroup.com/nsn/5315-01-467-2428>

First End Style:

Chamfered w/thru hole

Second End Style:

Chamfered

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.188 inches and 0.190 inches

Distance From Centerline Of Hole To End Of Pin:

0.300 inches

End Application:

End item 014553174, striker, xm707

First End Taper Length:

0.120 inches

Second End Taper Length:

0.560 inches

Second End Relationship With First End:

Not identical

First End Location:

Chamfered end

First End Taper Angle:

Between 40.0 degrees and 50.0 degrees

Second End Tip Radius:

0.1875 inches

Second End Taper Angle:

60.0 degrees

Special Features:

length 4.08 inches ly; first end length 1.12 inches ly; groove width 0.062 inches ly; first end width, 0.562 inches ly; second end diameter, 0.5000 inches ly; hole diameter 0.188 inches ly; all edges and corners shall be free from burrs and sharp edges; heat treat per mil-h-6875, condition h1075; finish 5.4.1 of mil-std-171; clean and passivate

Material:

Stainless steel

Material Specification:

Ams5643, cond.A assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response and mil-std-171 military standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0