

View Online at <https://aerobasegroup.com/nsn/5315-01-467-6084>

First End Style:

Split

Second End Style:

Chamfered w/thru hole

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.375 inches and 0.439 inches

Pinlength:

Between 0.970 inches and 1.030 inches

Pindiameter:

0.3750 inches

Second End Taper Length:

Between 0.003 inches and 0.015 inches

Thready Qty Per Inch (tpi):

24.0

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

First End Location:

Slot end

Pin Grip Length:

0.570 inches

Second End Taper Angle:

Between 10.0 degrees and 20.0 degrees

Product Name:

Pin, mounting

Special Features:

Light armored vehicle; first end style, tapered with slotted center; angeles on first end 15 degrees +/- 5 degrees; diameter at tapered first end 0.240 ly; slot at first end 0.050 ly; sharp edges and corners shall be broken 0.003 to 0.015 unless otherwise specified

Material:

Stainless steel

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-std-171 spec.