

View Online at <https://aerobasegroup.com/nsn/5315-01-467-6084>

**First End Style:**

Split

**Second End Style:**

Chamfered w/thru hole

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.375 inches and 0.439 inches

**Pinlength:**

Between 0.970 inches and 1.030 inches

**Pindiameter:**

0.3750 inches

**Second End Taper Length:**

Between 0.003 inches and 0.015 inches

**Thready Qty Per Inch (tpi):**

24.0

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Slot end

**Pin Grip Length:**

0.570 inches

**Second End Taper Angle:**

Between 10.0 degrees and 20.0 degrees

**Product Name:**

Pin, mounting

**Special Features:**

Light armored vehicle; first end style, tapered with slotted center; angeles on first end 15 degrees +/- 5 degrees; diameter at tapered first end 0.240 ly; slot at first end 0.050 ly; sharp edges and corners shall be broken 0.003 to 0.015 unless otherwise specified

**Material:**

Stainless steel

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-std-171 spec.