

View Online at <https://aerobasegroup.com/nsn/5315-01-468-3766>

Shank Diameter:

0.312 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Pull and push

Shear Strength:

14400 double pounds per square inch

Shoulder To Head End Distance:

0.935 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.410 inches

Special Features:

tensile strength 510 psi

Material:

Stainless steel spindle

Material Specification:

Qq-s-763 federal specification 2nd material response head or astm a484 assn standard 2nd material response head or astm a582 assn standard 2nd material response head

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification 3rd treatment response head

Style Designator:

Ring handle

Test Data Document:

96906-ms17990-513 standard (includes industry or association standards, individual manufactureer standards, etc.).

Specification Data:

96909-nas-17990 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.