

View Online at <https://aerobasegroup.com/nsn/5315-01-468-3766>

**Shank Diameter:**

0.312 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.300 inches and 1.320 inches

**Actuation Type:**

Pull and push

**Shear Strength:**

14400 double pounds per square inch

**Shoulder To Head End Distance:**

0.935 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.410 inches

**Special Features:**

tensile strength 510 psi

**Material:**

Stainless steel spindle

**Material Specification:**

Qq-s-763 federal specification 2nd material response head or astm a484 assn standard 2nd material response head or astm a582 assn standard 2nd material response head

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification 3rd treatment response head

**Style Designator:**

Ring handle

**Test Data Document:**

96906-ms17990-513 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Specification Data:**

96909-nas-17990 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.