

View Online at <https://aerobasegroup.com/nsn/5315-01-469-0292>

First End Style:

Chamfered

Second End Style:

Chamfered w/thru hole

Shank Length:

Between 0.220 inches and 0.280 inches

Shoulder Diameter:

Between 0.376 inches and 0.377 inches

Shank Diameter:

Between 0.375 inches and 0.376 inches

Overall Length:

Between 0.870 inches and 0.930 inches

End Application:

Light armored vehicle

First End Taper Length:

0.030 inches

Second End Taper Length:

0.120 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

56.0 rockwell c

First End Location:

Long end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

Between 28.0 degrees and 32.0 degrees

Product Name:

Pin, straight, headless

Special Features:

Rshank head conical; heat treatment mil-h-6875, quench and temper at a temperature of 450 degrees; finish clean and passivate 5.4.1 of mil-std-171; all fillet radii shall be .005 to .030 unless otherwise specified

Material:

Stainless steel

Material Specification:

Ams5630, class440c assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-std-171 spec.