

View Online at <https://aerobasegroup.com/nsn/5315-01-470-3637>

**Grip Length:**

0.875 inches

**Overall Width:**

1.020 inches

**Actuation Method:**

Handle

**Pin Diameter:**

0.250 inches

**Shoulder To Head End Distance:**

1.000 inches

**Product Name:**

Adjustable diameter pin

**Special Features:**

Hex socket for adgustment; if anodized, die black; dry film lube per mil-l-46010, ty1; heat treat to rc40min; actuation of cam handle for drawing up of bushing to be 180 degrees max; handle material only is alluminum alloy per qq-a-200/8 or qq-a-225/8; pin, bushing assembly, set screw, barrel nut and washer cres 17-4 per ams 5643; lanyard, lockring and locking cam handle optional

**Material:**

Steel comp 630

**Surface Treatment:**

Cadmium or passivate or anodize

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response or qq-p-35 federal specification single treatment response or mil-4-8625, ty3, cl2 military specification single treatment response

**Style Designator:**

Closed position

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-4-8625 spec.