## NSN 5315-01-471-1893

First End Style:

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-471-1893

| Chamfered  |
|--|
| Second End Style:                                    |
| Chamfered w/thru hole                                |
| Thread Class:  |
| 3a   |
| Thread Direction:                                    |
| Right-hand   |
| Thread Length:                                       |
| 1.130 inches   |
| Shoulder Diameter:                                   |
| 1.000 inches   |
| Overall Length:                                      |
| 5.250 inches   |
| First Step Diameter:                                 |
| 0.663 inches   |
| Second Step Diameter:                                |
| Between 0.620 inches and 0.625 inches                |
| Second Step Length:                                  |
| 1.000 inches   |
| Third Step Diameter:                                 |
| Between 0.435 inches and 0.436 inches                |
| Third Step Length:                                   |
| 1.380 inches   |
| Hole Arrangement Style:                              |
| One end drilled                                      |
| First Hole Diameter:                                 |
| 0.150 inches   |
| Distance From Centerline Of Hole To End Of Pin:      |
| 0.200 inches   |
| End Application:                                     |
| Adapter pack, vertical stabilizer, attack helicopter |
| Shoulder Length:                                     |
| 1.740 inches   |
| First End Taper Length:                              |
| 0.100 inches   |
| Second End Taper Length:                             |
| 0.030 inches   |
| Thready Qty Per Inch (tpi):                          |
| 16   |
| Second End Relationship With First End:              |

Not identical

## NSN 5315-01-471-1893

Headless Shoulder Pin - Page 2 of 2



| Thread Size:  |
|---|
| 0.750 inches  |
| First End Location:                                   |
| Unthreaded end  |
| First End Taper Angle:                                |
| 45.0 degrees  |
| Second End Taper Angle:                               |
| 45.0 degrees  |
| Material:   |
| Steel comp 630  |
| Material Specification:                               |
| Ams5643, conda assn standard single material response |
| Style Designator:                                     |
| Shoulder  |
| Thread Series Designator:                             |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |
| No  |
| Fiig:   |
| A212a0  |