

View Online at <https://aerobasegroup.com/nsn/5315-01-474-8472>

First End Style:

Chamfered

Second End Style:

Chamfered w/thru hole

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.030 inches

Shoulder Diameter:

0.156 inches

Shank Diameter:

0.125 inches

Overall Length:

0.340 inches

End Application:

Command launch unit

First End Taper Length:

0.510 inches

Second End Taper Length:

0.130 inches

Thready Qty Per Inch (tpi):

48

Second End Relationship With First End:

Not identical

Thread Size:

0.112 inches

Second Shank Diameter:

0.125 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

45.0 degrees

Second Shank Length:

Between 0.020 inches and 0.030 inches

Product Name:

Pin, drive

Special Features:

Machine corner radius .01 max; threads per federal standard 428, us customary units, no metric

Material:

Steel comp 303

Material Specification:

Astma582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-186, code 216 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-std-186 spec.