

View Online at <https://aerobasegroup.com/nsn/5315-01-474-8472>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered w/thru hole

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.030 inches

**Shoulder Diameter:**

0.156 inches

**Shank Diameter:**

0.125 inches

**Overall Length:**

0.340 inches

**End Application:**

Command launch unit

**First End Taper Length:**

0.510 inches

**Second End Taper Length:**

0.130 inches

**Thready Qty Per Inch (tpi):**

48

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.112 inches

**Second Shank Diameter:**

0.125 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

Between 0.020 inches and 0.030 inches

**Product Name:**

Pin, drive

**Special Features:**

Machine corner radius .01 max; threads per federal standard 428, us customary units, no metric

**Material:**

Steel comp 303

**Material Specification:**

Astma582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-186, code 216 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-std-186 spec.