NSN 5315-01-475-1830

Threaded Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-475-1830 First End Style: Chamfered Second End Style: Slotted **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.177 inches Pinlength: 1.095 inches Pindiameter: 0.9340 inches **End Application:** Command launch unit Second End Slot Width: 0.050 inches First End Taper Length: 0.015 inches **Second End Slot Depth:** 0.065 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.086 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees Pin Grip Length: 0.918 inches **Product Name:** Pin, hinge, threaded **Special Features:** Pin is headed with a slot 0.035 deep and diameter of 0.188 inches;

Material: Steel comp 303

Material Specification:

Astma582 assn standard single material response

NSN 5315-01-475-1830

Threaded Straight Pin - Page 2 of 2



| Surface Treatment: |
|--|
| Passivate |
| Surface Treatment Specification: |
| Mil-std-186 military specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| Mil-std (military Standard): |

Mil-std-186 spec.