

View Online at <https://aerobasegroup.com/nsn/5315-01-475-5120>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Chamfer Length:**

0.078 inches

**Diameter:**

Between 0.371 inches and 0.373 inches

**Under Head Length:**

1.969 inches

**Pin Chamfer Angle:**

15.0 degrees

**Shear Strength:**

16160 double pounds per square inch

**Pin Head Diameter:**

0.500 inches

**Special Features:**

Item altered fromms20392 no cadmium plating; shank end of pins may be chamfered or a radius of .031; pins shall be free of burrs and sharp edges; drilled hole on shank end of pin 0.108 in diameter placed 1.719 inches from under head; surface treatment zinc per astm b633, type 2, supplementary chromate treatment, normal color not bleached or clear

**Height:**

0.062 inches

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:**

Ams6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astmb633, type 2 assn standard single treatment response and mil-std-171 military specification single treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.