NSN 5315-01-475-5120

Headed Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-475-5120 **Head Style:** Pan no. 2 (r1 not required in item description) **Chamfer Length:** 0.078 inches Diameter: Between 0.371 inches and 0.373 inches **Under Head Length:** 1.969 inches Pin Chamfer Angle: 15.0 degrees **Shear Strength:** 16160 double pounds per square inch Pin Head Diameter: 0.500 inches **Special Features:** Item altered fromms20392 no cadmium plating; shank end of pins may be chamfered or a radius of .031; pins shall be free of burrs and sharp edges; drilled hole on shank end of pin 0.108 in diameter placed 1.719 inches from under head; surface treatment zinc per astm b633, type 2, supplemantary chromate treatment, normal color not bleached or clear Height: 0.062 inches Material: Steel comp 4037 or steel comp 4130 or steel comp 8630 **Material Specification:** Ams6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astmb633, type 2 assn standard single treatment response and mil-std-171 military specification single treatment response **Style Designator:** Straight Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.