## NSN 5315-01-475-9921

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-475-9921

V	iew Online at https://aerobasegroup.com/nsn/5315-01-475-9921
F	irst End Style:
С	hamfered
Н	lead Style:
Р	an no. 2 (r1 not required in item description)
U	nder Head Length:
В	etween 5.180 inches and 5.200 inches
F	irst Step Diameter:
В	etween 0.980 inches and 1.003 inches
F	irst Step Length:
В	etween 3.147 inches and 3.167 inches
S	econd Step Diameter:
В	etween 0.855 inches and 0.865 inches
S	econd Step Length:
В	etween 1.560 inches and 1.580 inches
Ε	nd Application:
M	ledium tactical vehicle
F	irst End Taper Length:
0	.090 inches
Н	ardness Rating:
3	4.0 rockwell c and 40.0 rockwell c
F	irst End Taper Angle:
4	5.0 degrees
P	in Head Diameter:
1.	.500 inches
Ρ	roduct Name:
Ρ	in, lower
S	pecial Features:
Z	inc plate with chromate overcoat; quench and temper; dimentions apply after plating
Н	eight:
0	.500 inches
M	laterial:
S	teel comp 4130
M	laterial Specification:
A	stma322 assn standard single material response
S	urface Treatment:
Z	inc and chromate
S	urface Treatment Specification:
	stmb633, type 2, classf assn standard single treatment response
	tyle Designator:
	houlder
	helf Life:
Ν	/a

N/a

## NSN 5315-01-475-9921

Headed Shoulder Pin - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A212a0