NSN 5315-01-477-5701

Headless Shoulder Pin - Page 1 of 2

cond b fscm 76301 mfr ref 3rd material response



View Online at https://aerobasegroup.com/nsn/5315-01-477-5701

First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.595 inches
Shoulder Width Across Flats:
Between 0.367 inches and 0.376 inches
Shank Diameter:
0.189 inches
Overall Length:
Between 1.097 inches and 1.117 inches
End Application:
Ac/dc power
Second End Taper Length:
0.190 inches
Thready Qty Per Inch (tpi):
32
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
Second Shank Diameter:
0.185 inches
First End Location:
Threaded end
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
0.312 inches
Special Features:
Corrosion resistant steel
Material:
Steel comp 302 or steel comp 304 or steel comp 303se
Material Specification:
Qq-s-763 cond b federal specification 1st material response or qq-s-763 cond b federal specification 2nd material response or mms265

NSN 5315-01-477-5701

Headless Shoulder Pin - Page 2 of 2



Surrace Treatment:
Passivate
Surface Treatment Specification:
Ams qq-p-35 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·

A212a0